



BATOR THERM

The new generation of folding doors.

Excellent heat insulation, and aesthetically pleasing – highly versatile, yet cost-effective.

THE BATOR THERM RANGE IN STEEL – HIGHLY VERSATILE AND EXTREMELY COST-EFFECTIVE.

AESTHETIC AND FUNCTIONAL

Simple operating controls, smooth surfaces with no obtrusive hinges and the glazing of your choice make the design particularly attractive.

INSTALLATION AND ASSEMBLY

Thanks to their CFC-free rigid foam core, these doors provide outstanding insulation. On-site installation time is very short as the door components are factory pre-assembled.

FITTING AND OPTIONS

THERM folding doors can be fitted in various ways: opening inwards, outwards or within the thickness of the reveal. The split and standard hinges are virtually invisible behind a rubber profile section, so the doors blend smoothly into any façade. Each section of the door can have a number of glazed panels inserted, of any size you wish. Alternatively, service or fire escape doors, ventilation fins or gratings can be incorporated.

SAFETY

Like all BATOR doors, THERM complies with EKAS (Federal Coordination Commission for Occupational Safety) guidelines and current EN standards.

COATING

All door systems can be supplied in any color. You can even specify different colors for certain components such as the door panels, frames, glass retaining strips and service doors.

MOTOR

As optional extras, THERM 2+2 folding doors can be fitted with an electric motor, contact mat, photoelectric barrier and radio receiver. The motor does not require an additional reveal.

ACCESSORIES

There is a wide range of additional fittings such as handles, locks, shoot bolts, weather strips, door retainers etc. to suit any configuration.

HIGH R VALUE

Thanks to its innovative design, the complete door installation has an excellent R value of 0.8.

PRODUCTION TIME

Thanks to our automated manufacturing process, a customised THERM door can – depending on the type of glass – be produced and ready for delivery within two to three weeks.

ONLINE CALCULATOR

Have you already registered with us? Then use our free online calculator at www.mybator.com to design your customised folding door with just a few clicks of the mouse, and obtain a quote for it in no more than a few seconds.

| | |
|-------------------------|--|
| MAX. DIMENSIONS* | |
| (W X H) | 34 ft x 17 ft |
| COLOR | any scheme |
| GLAZING | max. 2 panels |
| MOTOR | 240V AC, 0.3 KW incl. control panel |
| SPEED* | 1 ft / sec. |
| OPTIONS | Contact mat Photoelectric barrier Service doors Weather boards Shoot bolts |

* Standard Conversion

For the latest information please visit www.batorusa.com



The hospital in Savognin opted for BATOR THERM sliding folding doors.

Saving lives by ensuring reliable and fast access for ambulances and fire engines.

North America Headquarters
BATOR (North America) LLC
125 South Elm Street, Ste. 405
Greensboro, NC 27401

Phone: 336.907.2286
Fax: 336.907.2287

usa@bator.com
www.batorusa.com

Corporate Headquarters
BATOR Industrietore AG
Hofmattstrasse 14
CH-3360 Herzogenbuchsee (Switzerland)

Phone +41 (0)62 956 12 12
Fax +41 (0)62 956 12 13

bator@bator.com
www.bator.com